

# MVB EPOXY COAT | SAFETY DATA SHEET (SDS)

## SECTION 1 IDENTIFICATION

<b>Product identifier</b>	MVB Epoxy Coat - Part A
<b>Other means of identification</b>	MVB Epoxy Coat
<b>Recommended use and restrictions on use</b>	Construction product / Refer to technical information
<b>Initial supplier identifier</b>	11530 Chairman Dr, Dallas, TX 75243 927.293.4444 contact@advancedresins.com
<b>Emergency telephone number/restriction on use</b>	Canada – CANUTEC 24 hour number 613-996-6666

## SECTION 2 HAZARD IDENTIFICATION

<b>Classification of hazardous product</b> (name of the category or subcategory of the hazard class)	Skin Sensitizer Category 1B Chronic aquatic toxicity Category 2 Acute aquatic toxicity Category 3 Acute toxicity Dermal Category 5
---	---

### Information elements

(symbols, signal words, hazard statements and precautionary statements of the category/subcategory)



- H313** May be harmful in contact with skin
- H317** May cause an allergic skin reaction
- H402** Harmful to aquatic life
- H411** Toxic to aquatic life with long lasting effects

**P101** If medical advice is needed, have product container or label at hand. **P102** Keep out of reach of children. **P103** Read label before use. **P261** Avoid breathing dust/fume/gas/mist/vapors/spray. **P272** Contaminated work clothing should not be allowed out of the workplace. **P280** Wear protective gloves/protective clothing/eye protection/face protection. **P273** Avoid release to the environment. **P302 + P352** IF ON SKIN: Wash with plenty of water. **P333 + P313** If skin irritation or a rash occurs: Get medical advice/attention. **P321** Specific treatment (see section 4 on this SDS). **P362 + P364** Take off contaminated clothing. And wash it before reuse. **P391** Collect spillage. **P312** Call a POISON CENTER/doctor if you feel unwell. **P501** Dispose of contents/ container to an approved waste disposal plant.

<b>Other Hazards Known</b>	None
----------------------------	------

## SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name (common name/synonyms)	CAS NUMBER or other	Concentration (%)
BISPHENOL A EPOXY RESIN	0025085-99-8	47 - 86
BISPHENOL F EPOXY RESIN	0028064-14-4	9 - 17
ETHYL HEXYL GLYCIDYL ETHER, 2-	0002461-15-6	8 - 14
BENZYL ALCOHOL	0000100-51-6	2 - 4
DIPROPYLENE GLYCOL METHYL ETHER ACETATE	0088917-22-0	1.7 - 3

All ingredients are listed according to OSHA (29 CFR).

\* Statement This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).

## SECTION 4 FIRST AID MEASURES

<b>Inhalation</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If exposed/feel unwell/concerned: Call a POISON CENTER/doctor.
<b>Ingestion</b>	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a doctor if you feel unwell.
<b>Skin contact</b>	IF ON SKIN: wash with plenty of water (15-20 minutes). IF SKIN irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.
<b>Eye contact</b>	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Most important symptoms and effects (acute and delayed)</b>	Causes severe skin, respiratory or digestive tract burns and eye damage.
<b>Indication of immediate medical attention/special treatment</b>	In all cases, call a doctor. Do not forget this document.

## SECTION 5 FIREFIGHTING MEASURES

<b>Specific hazards of the hazardous product (hazardous combustion products)</b>	Excessive pressure or temperature may cause explosive rupture of containers.
<b>Suitable and unsuitable extinguishing media</b>	In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish surrounding products.
<b>Special protective equipment and precautions for fire-fighters</b>	During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

<b>Personal precautions, protective equipment and emergency procedures</b>	Absorb spillage to prevent material-damage. Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).
<b>Methods and materials for containment and cleaning up</b>	Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

### Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: None known

### Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

### Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance / color	Clear liquid	Vapour pressure	Not available
Odour	Odorless	Vapour density	Not available
Odour threshold	Not available	Relative density	9.35 lb/gal
pH	Not available	Solubility	Not available
Melting point / Freezing point	Not available	Partition coefficient of n-octanol/water	Not available
Initial boiling point/ranges	Not available	Auto-ignition temperature	Not available
Flash point	> 199.4°F (93°C)	Decomposition temperature	Not available
Evaporation rate	Not available	Viscosity	Not available
Flammability (solid, gas)	Not available	VOC	0.47 lb/gal
Upper/Lower flammability or explosive limits	Not available	Other	None know

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	Does not react under the recommended storage and handling conditions prescribed.
<b>Chemical Stability</b>	Stable under the recommended storage and handling conditions prescribed.
<b>Possibility of hazardous reactions</b>	None known
<b>Conditions to avoid</b> (static discharge, shock or vibration)	Heat, high temperature, open flame, sparks, and moisture. Contact with incompatible materials in a closed system will cause buildup of pressure.
<b>Incompatible materials</b>	Oxidizing materials; etc.
<b>Hazardous decomposition products</b>	Combustion products: organic vapors and thermal decomposition fragments.

## SECTION 11 TOXICOLOGICAL INFORMATION

<b>Information on the likely routes of exposure</b> (inhalation, ingestion, skin and eye contact)	May be harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing;
<b>Delayed and immediate effects</b> (chronic effects from short-term and long-term exposure)	Skin Sensitization – Possible; Respiratory Sensitization – Exposure may cause mucous membrane and respiratory tract irritation, tightness of chest, headache, shortness of breath, and a dry cough. The effects of acute exposure may be delayed in onset up to 12-24 hours. Repeated exposure above current occupational limits may cause an allergic sensitization of the respiratory tract. This is characterized by an asthma-like response upon re-exposure to the chemical. The symptoms may include coughing, wheezing, shortness of breath and chest tightness. May cause an allergic skin reaction; Germ Cell Mutagenicity – No data available; Carcinogenicity – No ingredient listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxicity – No data available; Specific Target Organ Toxicity — Single Exposure – No data available; Specific Target Organ Toxicity — Repeated Exposure – Repeated exposure generally aggravates the following medical conditions : Cardiovascular disease and Chronic respiratory disease.; Aspiration Hazard – No data available; Health Hazards Not Otherwise Classified – No data available.
<b>Acute toxicity</b>	Ingestion : Irritation or chemical burns of the mouth, pharynx, esophagus and stomach can develop following ingestion. 0000100-51-6 BENZYL ALCOHOL; LC50(Inhalation, rat): >500 mg/m <sup>3</sup> ; Toxic effects: Behavioral - somnolence (general depressed activity) Behavioral - ataxia Lungs, Thorax, or Respiration - respiratory depression; LD50(Dermal, rabbit): 2000 mg/kg; LD50(Oral, rat): 1230 mg/kg; Toxic effects: Behavioral - somnolence (general depressed activity) Behavioral - excitement Behavioral - coma

## SECTION 12 ECOLOGICAL INFORMATION

<b>Ecotoxicity</b> (aquatic and terrestrial information)	Harmful to aquatic life. Toxic to aquatic life with long lasting effects
<b>Persistence and degradability</b>	No data available
<b>Bioaccumulative potential</b>	No data available
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	No data available

## SECTION 13 DISPOSAL CONSIDERATIONS

**Information on safe handling for disposal/methods of disposal/contaminated packaging**  
Dispose of contents/container into safe container in accordance with local, regional or national regulations.

## SECTION 14 TRANSPORT INFORMATION

### UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN); CLASS 9; PG III

### UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN); CLASS 9; PG III

### UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN); CLASS 9; PG III

**Special Precautions (transport/conveyance):** May also be shipped as a LIMITED QUANTITY in accordance with TDG.

**Environmental hazards (IMDG or other):** Marine Pollutant

**Bulk transport (usually more than 450L in capacity):** Possible

## SECTION 15 REGULATORY INFORMATION

<b>Safety/health Canadian regulations specifics</b>	Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).
<b>Environmental Canadian regulations specifics</b>	Refer to Section 3 for ingredient(s) of the DSL
<b>Safety/health/environmental outside regulations specifics</b>	United States OSHA information: This product is regulated according to OSHA (29 CFR). United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14. United States TCSA information: Refer to the ingredients listed in Section 3.
<b>Bioaccumulative potential</b>	
<b>National Fire Protection Association (NFPA)</b>	HEALTH: 3 FLAMMABILITY: 1 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3. HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## SECTION 16 OTHER INFORMATION

<b>Date of the latest revision of the safety data sheet</b>	February 4, 2020 version 5
<b>Corrections</b>	SDS Template modifications
<b>References</b>	Safety Data Sheets from manufacturer/supplier
<b>Abbreviations</b>	<b>ACGIH</b> American Conference of Governmental Industrial Hygienists <b>ATE</b> Acute toxicity estimate <b>CAS</b> Chemical Abstract Service <b>DSL</b> Domestic Substance List <b>IARC</b> International Agency for Research on Cancer <b>IATA</b> International Air Transport Association <b>IMDG</b> International Maritime Dangerous Goods Code <b>LC</b> Lethal concentration <b>LD</b> Lethal Dosage <b>NIOSH</b> National Institute for Occupational Safety and Health <b>NTP</b> National Toxicology Program (U.S.A.) <b>OSHA</b> Occupational Safety and Health Administration (U.S.A.) <b>PEL</b> Permissible Exposure Limit <b>STEL</b> Short-term Exposure Limit <b>TDG</b> Transport of dangerous goods in Canada <b>TLV</b> Threshold Limit Value <b>TSCA</b> Toxic Substances Control Act <b>TWA</b> Time Weighted Average <b>WHMIS</b> Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.